

# KP-C60P CUMMINS GENSET

POWERED BY 4BTA3.9-G2

Leroy Somer LSA42.3 L9

Power 60 KVA



**Gainwealth Machinery Sdn Bhd**

No. 6, Jalan Sutera 1/5A Kawasan Perindustrian, Bukit Angkat, 43000 Kajang, Selangor, Malaysia

H/P: 6012-3717349 Tel: 03-8730 1327

E-mail: alex2gw@gmail.com

# SPECIFICATIONS

## FEATURES:

- Composed of CUMMINS diesel engine and Stamford or Leroy Somer or Keypower brushless alternator
- 24V DC start motor and storage battery
- Brushless, Self-excited, IP23, insulation class H alternator
- 50°C radiator as standard
- Key start panel control system as standard, digital auto-start panel is optional
- Base fuel tank
- Optional open type or silent type
- All generator sets are gone through rigorous testing before being released to the market place, including 50% load, 75% load, 100% load, 110% load and all protection function (overspeed stop, high water temperature, low oil pressure, battery charging fail, emergency stop)

GENSET MODEL	Genset Specification					Engine Specification				Alternator Model
	KVA		Cons 100% (L/H)	dB(A) @7m	Tank (L)	Model	Cyl.	Gov.	Asp.	
	ESP	PRP								
KP-C60P	66	60	13.8	71	250	4BTA3.9-G2	4	E	TW	LSA42.3 L9

- 1) Available in various voltages
- 2) To show KEYPOWER Generating Sets Model

KP-C60P, it is the Prime power 60kva generating set.

- 3) ESP=Standby power standby duty, operation under variable load, without overload.  
PRP=Prime power continuous duty operation, under variable load, 10% overload permissible 1/12hr.

4) E=Electronic speed governor;

M=Mechanical speed governor

5) Asp=Aspiration;

NA=Naturally Asp;

TC=Turbocharged;

TW=Turbocharged after cooled;

TCA= Turbocharged air-air after cooled

6) Technical data is subject to work test conditions

## PERFORMANCE RELIABLE:

Voltage regulation

Voltage regulation maintained within  $\pm 0.5\%$  as follow:

- Power factor Between 0.8~1.0 lag
- From no load to full load, any steady load
- Speed droop variation under 4.5%

Frequency/Speed undulation

- Change load from 0-100%, Frequency/Speed Droop Ratio within 5%.
- Load from 25-100%, any steady load Frequency/Speed undulation within 1.5%


Effect factor of telecom

- TIF(MA MG1-22) better than 50
- THF( BS EN60034) better than 2%

## CRITERION

- ISO8528, GB/T2820
- EN12601:2001, EN60034-22:1997, EN60204-1:2006
- ISO9001:2000 QUALITY CONTROL SYSTEM

## DIMENSION & WEIGHT



### Open Type

Overall size (L\*W\*H)

1750\*860\*1375

Weight: 950kg

### Silent Type

Overall size (L\*W\*H)

2602\*1100\*1526

Weight: 1430kg

# ENGINE SPECIFICATION

## CUMMINS DIESEL ENGINE

Engine Model	4BTA3.9-G2
Number of Cylinders	4
Cylinder arrangement	Vertical in-line
Cycle	Four stroke
Aspiration	Turbocharged aftercooled
Bore×Stroke (mm×mm)	102*120
Displacement (Liter)	3.9
Compression Ratio	17.5:1
Prime Power/Speed (kW/rpm)	58/1500RPM
Standby Power/Speed (kW/rpm)	64/1500RPM
Speed Governor	Electronic
Cooling System	Water-cooled, 50 °C radiator as standard
Speed Stability (%)	≤3%
Total lubrication system capacity (L)	10.9
Coolant capacity (without radiator) (L)	7.9
Fuel Consumption at 100% Load (L/H)	13.8
Starter Motor	DC24V
Start type	Electrical

## TECHNICAL DATA

Alternator Model	LSA42.3 L9
Exciter type	Brushless, Self-excited
Power factor	0.8
Voltage Adjust range	≥5%
Voltage Regulation NL-FL	≤±1.0%
Insulation Grade	H
Protection Grade	IP23

# CONTROL SYSTEM

Providing the standard functions as follows:

(Also can be made according to the customers' special requirements)

- \* Automatic Start/Stop
- \* Settings can be adjustable via key buttons on front panel
- \* 3 start attempts failure and Automatic Crank Disconnect
- \* Parameters display (V/A/Hz/Hour)
- \* Engine monitoring and protection
- \* Charge alternator exciting and Charge alternator fail alarm
- \* Running hour counting
- \* Emergency stop pushbutton
- \* Alarm System: Over speed、 High Engine Temperature  
Low Oil Pressure、 Charge Fail

\* Protection System: Over speed、 High Engine Temperature、 Low Oil Pressure、 Emergency Stop. And the other protection function pre-setting

Digital Auto-start Generator controller integrating digital, intelligent and network techniques is used for automatic control system of diesel generator. It can carry out functions including automatic start/stop, data measure and alarming. Optionally assembled with the ATS, it can carry out auto-switching between the outer power and generating set power. (AMF)

**2. Option: Deepsea DSE7320 AMF Digital Auto Start**

**3. Option: ComAp AMF25 Digital Auto Start**

**4. Option: Deepsea DSE3110 Digital Auto Start**



(1) 6120



(2) DSE7320



(3) AMF25



(4) DSE3110

